



**PB200 part B**



**Penntek Industrial Coatings, 7850 Lakeville BLVD, Lakeville, MN 55044**  
 24-hour Emergency Phone: 1-800-535-5053

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**MANUFACTURER'S NAME: PENNTEK INDUSTRIAL COATINGS**

**ADDRESS:** 7580 LAKEVILLE BLVD  
 LAKEVILLE, MN 55044

**EMERGENCY PHONE: 1-800-535-5053**

**INFORMATION PHONE: 952-236-9305**

**HMIS CODES: H F R P**

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Component/Exposure Limits</b>	<b>CAS#</b>	<b>% by Wt.</b>
ZEOLITE	1318-02-1	.00
Diphenylmethane 4,4'-diisocyanate	101-68-8	30 -60
Diphenylmethanediisocyanate, isomers and homologues	9016-87-9	13 -30
Isocyanates, reaction product of polyol with methylenediphenyl diisocyanate	Proprietary	13 -30

**3. HAZARDS IDENTIFICATION**

**Potential Health Effects**

**EYE:** Irritating to eyes  
 MAY CAUSE EYE IRRITATION. DIRECT CONTACT MAY CAUSE STINGING, TEARING AND REDNESS.

**SKIN:**  
 \*\*\*WARNING\*\*\* AVOID ALL CONTACT WITH SKIN. PENETRATES SKIN READILY. ANY CONTACT MAY RESULT IN THE ABSORPTION OF POTENTIALLY HARMFUL AMOUNTS WHICH CAN CAUSE DAMAGE TO THE KIDNEYS, LIVER, BLOOD AND/OR BONE MARROW.

REPEATED OR PROLONGED SKIN CONTACT WITH THE SOLVENT CAN RESULT IN DRY, DEFATTED AND CRACKED SKIN CAUSING INCREASED SUSCEPTIBILITY TO INFECTION. IN ADDITION, IRRITATION (I.E. REDNESS AND SWELLING) THAT MAY DEVELOP INTO DERMATITIS CAN OCCUR FROM SKIN CONTACT. SOLVENTS CAN PENETRATE THE SKIN AND MAY CAUSE EFFECTS SIMILAR TO THOSE IDENTIFIED UNDER ACUTE INHALATION SYMPTOMS.

**INGESTION:**  
 MODERATELY TOXIC. MAY CAUSE MOUTH, THROAT, ESOPHAGUS AND STOMACH IRRITATION, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

**INHALATION:**  
 HIGH VAPOR/AEROSOL CONCENTRATIONS (GREATER THAN APPROXIMATELY 1000 PPM) ARE IRRITATING TO THE EYES AND THE RESPIRATORY

**PB200 part B**

Penntek Industrial Coatings, 7850 Lakeville BLVD, Lakeville, MN 55044  
24-hour Emergency Phone: 1-800-535-5053

TRACT, MAY CAUSE HEADACHES, DIZZINESS, ANESTHESIA, DROWSINESS, UNCONSCIOUSNESS, AND OTHER CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DEATH.

CHRONIC EXPOSURE TO ORGANIC SOLVENTS HAS BEEN ASSOCIATED WITH VARIOUS NEUROTOXIC EFFECTS INCLUDING PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. SYMPTOMS INCLUDE LOSS OF MEMORY, LOSS OF INTELLECTUAL ABILITY AND LOSS OF COORDINATION. MAY CAUSE SENSITIZATION BY INHALATION AND SKIN CONTACT. THIS PRODUCT IS A RESPIRATORY IRRITANT AND POTENTIAL RESPIRATORY SENSITISER: REPEATED INHALATION OF VAPOUR OR AEROSOL AT LEVELS ABOVE THE OCCUPATIONAL EXPOSURE LIMIT COULD CAUSE RESPIRATORY SENSITISATION. A HYPER-REACTIVE RESPONSE TO EVEN MINIMAL CONCENTRATIONS OF DIISOCYANATES MAY DEVELOP IN SENSITISED PERSONS. THE ONSET OF THE RESPIRATORY SYMPTOMS MAY BE DELAYED FOR SEVERAL HOURS AFTER EXPOSURE.!

OVEREXPOSURE TO VAPOR, DUST OR MIST MAY AGGRAVATE EXISTING RESPIRATORY CONDITIONS, SUCH AS ASTHMA, BRONCHITIS, AND INFLAMMATORY OR FIBROTIC RESPIRATORY DISEASE.

#### **MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE**

#### **CHRONIC (CANCER) INFORMATION:**

INFORMATION NOT AVAILABLE

#### **TERATOLOGY (BIRTH DEFECT) INFORMATION:**

INFORMATION NOT AVAILABLE

#### **REPRODUCTION INFORMATION:**

INFORMATION NOT AVAILABLE

**CARCINOGENICITY: NTP CARCINOGEN: NO**

**IARC MONOGRAPHS: NO**

**OSHA REGULATED: NO**

#### **4. FIRST AID MEASURES**

**EYES:** IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

**SKIN:** After contact with skin, wash immediately with plenty of warm soapy water. Get medical attention if irritation develops. Wash clothing before reuse. Clean shoes thoroughly before reuse. An MDI study has demonstrated that a polyglycol-based skin cleanser or corn oil may be more effective than soap and water.!

**INGESTION:** Wash out mouth with water. Move exposed person to fresh air. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur. Never give anything by mouth to an unconscious person.

IF SWALLOWED, GIVE 2 GLASSES OF WATER TO DRINK. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SEE A PHYSICIAN.

**INHALATION:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical attention immediately. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is laboured, oxygen should be administered by qualified personnel.

RESCUERS SHOULD PUT ON APPROPRIATE PROTECTIVE GEAR. REMOVE FROM AREA OF EXPOSURE.

**NOTE TO PHYSICIANS:** Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

#### **5. FIRE FIGHTING MEASURES**



**PB200 part B**

Penntek Industrial Coatings, 7850 Lakeville BLVD, Lakeville, MN 55044  
24-hour Emergency Phone: 1-800-535-5053

FROM HEAT, SPARKS AND FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE AND UPRIGHT TO PREVENT LEAKAGE.

**OTHER PRECAUTIONS:**

AVOID CONTACT WITH SKIN OR EYES. WASH THOROUGHLY AFTER HANDLING.

HOT ORGANIC CHEMICAL VAPORS OR MISTS ARE SUSCEPTIBLE TO SUDDEN SPONTANEOUS COMBUSTION WHEN MIXED WITH AIR. IGNITION MAY OCCUR AT TEMPERATURES BELOW THOSE PUBLISHED IN THE LITERATURE AS "AUTOIGNITION" OR "IGNITION" TEMPERATURES. IGNITION TEMPERATURES DECREASE WITH INCREASING VAPOR VOLUME AND VAPOR/AIR CONTACT TIME, AND ARE INFLUENCED BY PRESSURE CHANGES. REACTS SLOWLY WITH WATER TO PRODUCE CARBON DIOXIDE WHICH MAY RUPTURE CLOSED CONTAINERS.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****ENGINEERING CONTROLS:**

USE LOCAL EXHAUST VENTILATION WITH A MINIMUM CAPTURE VELOCITY OF 100 FT/MIN. (0.5 M/SEC.) AT THE POINT OF VAPOR EVOLUTION. REFER TO THE CURRENT EDITION OF INDUSTRIAL VENTILATION: A MANUAL OF RECOMMENDED PRACTICE PUBLISHED BY THE AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS FOR INFORMATION ON THE DESIGN, INSTALLATION, USE, AND MAINTENANCE OF EXHAUST SYSTEMS.

**RESPIRATORY PROTECTION:**

DO NOT BREATHE VAPORS. WHEN CONCENTRATIONS EXCEED THE ESTABLISHED EXPOSURE LIMITS, WEAR AN APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) UNTIL VAPORS ARE EXHAUSTED. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR RESPIRATOR USE. OBSERVE OSHA STANDARD 29CFR 1910.134.

**VENTILATION:**

PROVIDE GENERAL CLEAN AIR DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP THE AIR CONTAMINANT CONCENTRATION BELOW THE LOWER EXPLOSION LIMIT AND BELOW CURRENT APPLICABLE EXPOSURE LIMITS. REFER TO OSHA STANDARD 1910.94.

**SKIN PROTECTION:**

USE SOLVENT IMPERMEABLE GLOVES TO AVOID CONTACT WITH PRODUCT.

**EYE PROTECTION:**

DO NOT GET IN EYES. USE SAFETY EYEWEAR WITH SPLASH GUARDS OR SIDE SHIELDS, CHEMICAL GOGGLES, FACE SHIELDS.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

AVOID CONTACT WITH SKIN. USE PROTECTIVE CLOTHING. PREVENT CONTACT WITH CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING, INCLUDING SHOES, BEFORE REUSE.

**WORK/HYGIENIC PRACTICES**

WASH AT THE END OF EACH WORKSHIFT AND BEFORE EATING, SMOKING, OR USING THE TOILET. USE APPROPRIATE HAND AND SKIN LOTIONS TO PROTECT THE SKIN.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**PB200 part B**

Penntek Industrial Coatings, 7850 Lakeville BLVD, Lakeville, MN 55044  
24-hour Emergency Phone: 1-800-535-5053

**BOILING POINT: 278-290F****MELTING POINT: INFORMATION NOT AVAILABLE****VAPOR DENSITY: HEAVIER THAN AIR****SOLUBILITY IN WATER: INSOLUBLE****SPECIFIC GRAVITY: .89****EVAPORATION RATE: SLOWER THAN BUTYL ACETATE****pH: INFORMATION NOT AVAILABLE****VAPOR PRESSURE: INFORMATION NOT AVAILABLE****ODOR: ORGANIC SOLVENT****APPEARANCE: INFORMATION NOT AVAILABLE****10. STABILITY AND REACTIVITY****CHEMICAL STABILITY (CONDITIONS TO AVOID):**

STABLE

**INCOMPATIBILITY:**

STRONG ACIDS AND STRONG OXIDIZING AGENTS.

**CONDITIONS TO AVOID:**

ELEVATED TEMPERATURES

SOURCES OF IGNITION

**HAZARDOUS DECOMPOSITION PRODUCTS:**

THERMAL DECOMPOSITION OR COMBUSTION CAN PRODUCE FUMES CONTAINING ORGANIC ACIDS, CARBON DIOXIDE AND CARBON MONOXIDE.

**HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.****11. TOXICOLOGICAL INFORMATION****EYE:**

INFORMATION NOT AVAILABLE

**SKIN:**

INFORMATION NOT AVAILABLE

**INGESTION:**

INFORMATION NOT AVAILABLE

**INHALATION:**

INFORMATION NOT AVAILABLE

**SUBCHRONIC: INFORMATION NOT AVAILABLE****CHRONIC/CARCINOGENICITY: INFORMATION NOT AVAILABLE****TERATOLOGY: INFORMATION NOT AVAILABLE**



**PB200 part B**



Penntek Industrial Coatings, 7850 Lakeville BLVD, Lakeville, MN 55044  
24-hour Emergency Phone: 1-800-535-5053

**REPRODUCTION: INFORMATION NOT AVAILABLE**

**MUTAGENICITY: INFORMATION NOT AVAILABLE**

## **12. ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION: INFORMATION NOT AVAILABLE**

**CHEMICAL FATE INFORMATION:**

## **13. DISPOSAL CONSIDERATIONS**

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. INCINERATE IN APPROVED FACILITY.

## **14. TRANSPORT INFORMATION (Not meant to be all inclusive)**

US DOT HAZARD CLASS: NON HAZARDOUS

## **15. REGULATORY INFORMATION**

(Not meant to be all inclusive - selected regulations represented)

### **U.S. FEDERAL REGULATIONS:**

INFORMATION NOT AVAILABLE

### **OSHA:**

THIS PRODUCT IS CONSIDERED HAZARDOUS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29CFR 1910.1200).

### **CERCLA: SARA HAZARD CATEGORY:**

THIS MATERIAL IS REGULATED UNDER THE COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT (CERCLA) AND THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) TITLE III SECTION 302. THIS MATERIAL IS OR CONTAINS CHEMICAL(S) LISTED IN 40 CFR TABLE 302.4 OR NONDESIGNATED RCRA ICR SUBSTANCE(S). (NONDESIGNATED ICR SUBSTANCES APPLY TO MATERIALS THAT WILL NOT BE REUSED.) RELEASE IN EXCESS OF ITS REPORTABLE QUANTITY MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER (1-800-424-8802) AND TO THE APPROPRIATE STATE AND LOCAL EMERGENCY RESPONSE ORGANIZATIONS.

### **SECTION 313:**

THIS PRODUCT CONTAINS A CHEMICAL WHICH IS LISTED IN SECTION 313 AT OR ABOVE DE MINIMIS CONCENTRATIONS.

Component/Exposure Limits

CAS#

% by Wt.

\*\*\* NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT \*\*\*

### **TOXIC SUBSTANCES CONTROL ACT: INFORMATION NOT AVAILABLE**

Component/Exposure Limits

CAS#

% by Wt.

\*\*\* NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT \*\*\*

### **INTERNATIONAL REGULATIONS:**



**PB200 part B**



Penntek Industrial Coatings, 7850 Lakeville BLVD, Lakeville, MN 55044  
24-hour Emergency Phone: 1-800-535-5053

**CANADIAN WHMIS:**

INFORMATION NOT AVAILABLE

**CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA): INFORMATION NOT AVAILABLE**

**EINECS: INFORMATION NOT AVAILABLE**

**STATE REGULATIONS:**

**NEW JERSEY**

THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT:

Component/Exposure Limits	CAS#	% by Wt.
*** NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT ***		

**PENNSYLVANIA**

THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%:

Component/Exposure Limits	CAS#	% by Wt.
*** NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT ***		

**CALIFORNIA**

THE CHEMICAL(S) NOTED BELOW AND CONTAINED IN THIS PRODUCT, ARE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER:

Component/Exposure Limits	CAS#	% by Wt.
*** NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT ***		

**VOLATILE ORGANIC COMPOUNDS: 0.00 lb/g1**

**16. OTHER INFORMATION**

**MSDS Status: INFORMATION NOT AVAILABLE**

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. IT DOES NOT CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OF THE INFORMATION CONTAINED HEREIN. ACTUAL CONDITIONS OF USE AND HANDLING ARE BEYOND SELLER'S CONTROL. USER IS RESPONSIBLE TO EVALUATE ALL AVAILABLE INFORMATION WHEN USING PRODUCT FOR ANY PARTICULAR USE AND TO COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS.

\*\*\*\*\*

The following boilerplate keys do not have matching boilerplate key prefixes in the MSDS Master Format file:

- EF01
- NP02